

# ISOTAPE



**ISONEM ISOTAPE** has been created with a special formula. It can be applied even underwater whether hot or cold, wet or dry. It creates a highly strong, flexible and water-repellent barrier by sealing water, air, and moisture. **ISONEM ISOTAPE** is UV-resistant, environmentally friendly, VOC-free and has a wide temperature range that can be used in extreme weather conditions. It can close almost everything like large holes, cracks, gaps, and leaks.

## FEATURES

- It is dimensions 150cm x 5 cm.
- It can make coating including underwater.
- It can be cut and used in pieces.
- It is very powerful and multi-purpose.

## USAGE AREAS

- Roof leaks, gutters,
- Taps,
- Boats, skis,
- Personal watercraft, canoes,
- Outdoor equipment,
- Caravans,
- PVC, sanitary pipeworks
- Sprinkler systems,
- Pools and spas,
- Windows, doors, walls,
- Ventilation ducts
- PVC, acrylic, metal, steel, copper, aluminum, wood, ceramic, porcelain, tiles, glass, rubber, fiberglass, plaster, plaster, stone, cement, concrete, shingle roofs, membranes, plastics, fabrics, vinyl and much more provides excellent adhesion to more surfaces.

## APPLICATION INFORMATION

Clean the surface which is the water leak and stick it. In deep water leaks, the tape is brought the pasty and the damaged area is filled. Then its surrounding is cleaned and the tape is stuck. It is disposable. When it is removed from the surface, it is not used again.

## TECHNICAL SPECIFICATIONS

- **Color** : Black
- **Product consumption** : It can be cut and used in parts according to the application surface.

## PACKAGING & STORAGE

- **Packaging** : 1.5 m roll, 12 pieces/parcel
- **Storage temperature (°C)** : 5 - 35 °C
- **Shelf life** : 24 months from date of production if stored in original, unopened, undamaged packages.
- **Storage condition** : Store tightly closed in a dry and cool place.

## ! IMPORTANT

After sticking the tape, press to on it min. 30 seconds.

Compressive strength:  
70 Psi, application from inside.  
15 Psi, application from outside

## APPLICATION CONDITIONS and RISKS

Things to consider during and after the application	The application surface must be clean.
Other ISONEM products recommended	X
Application temperature	Do not apply at temperatures above 60°C.



## General Features



Environmentally Friendly



UV Resistance



Waterproof



Excellent Adhesion

